

SAFETY DATA SHEET.



Issuing date 11-Jul-2014

Revision Date 11-Jul-2014

Version 1.01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 19900 BAN-RUST TRI

Recommended use of the chemical and restrictions on use

Product code 19900

Product Type Extremely flammable aerosol
Synonyms None

Supplier's details

Recommended Use Rust preventative.
Uses advised against No information available

Supplier Address

Lawson Products, Inc.
8770 W. Byrn Mawr Avenue-Suite 900
Chicago, IL 60631-3515
773-304-5050

Emergency telephone number

Company Emergency Phone Number 888-426-4851

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 1
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated



Appearance Clear

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Wash hands thoroughly after handling
Wear protective gloves
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Do not spray on an open flame or other ignition source
Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Protect from sunlight. Store in a well-ventilated place
Keep container tightly closed.
Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
PETROLEUM DISTILLATES	64742-47-8	34.11765
KEROSENE	8008-20-6	28.50209
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	17.05882
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	14.70588
2-BUTOXYETHANOL	111-76-2	2.55882

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	Avoid contact with skin, eyes, and clothing. Avoid breathing, vapors, mist, or gas.
Eye contact	Immediately flush with plenty of water. Get medical attention if irritation persists.
Skin contact	Wash skin with soap and water. Get medical attention if irritation persists.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms	May cause skin irritation. Inhalation causing Central Nervous System effects. Ingestion causing lung damage.
----------------------	--

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

water fog. Dry chemical. Carbon dioxide (CO₂). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Flammable or extremely flammable aerosol. Container may burst in fire.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS.

Environmental precautions

Environmental precautions Report spills as required by local and federal regulations.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Contain liquid and collect with an inter,non-combustible material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible products Store away from strong oxidizers and acids.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
KEROSENE 8008-20-6	TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures Skin - potential significant contribution to overall exposure by the cutaneous route	-	TWA: 100 mg/m ³
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m ³
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls**Engineering Measures**

Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Safety glasses with side-shields.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties**Physical state**

Aerosol

Appearance

Clear

Color

amber

Odor

Solvent

Odor Threshold

No information available

Property**Values****Remarks • Methods****pH**

No information available

Melting/freezing point

No information available

Boiling point/boiling range

No information available

Flash Point

-96.4 °C / -141 °F

Based on propellant

Evaporation rate

No information available

Flammability (solid, gas)

No information available

Flammability Limits in Air**upper flammability limit**

No information available

lower flammability limit

No information available

Vapor pressure

No information available

Vapor density

No information available

Specific Gravity

0.804

Water solubility

Practically insoluble

Partition coefficient: n-octanol/water

No information available

Autoignition temperature

No information available

Not applicable

Decomposition temperature

No information available

Viscosity

No information available

Explosive properties

No information available

Other information**VOC Content(%)**

80.45

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Store away from strong oxidizers and acids.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Product does not present an acute toxicity hazard based on known information

Inhalation

Exposure to high vapour concentrations may cause nervous systems effects such as headache, nausea, and dizziness.

Eye contact

May cause slight irritation.

Skin contact

Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.

Ingestion

Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PETROLEUM DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
KEROSENE 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
2-BUTOXYETHANOL 111-76-2	= 470 mg/kg (Rat)	= 220 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h

Information on toxicological effects**Symptoms**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause mild irritation. Irritating to skin. Prolonged or repeated exposure may cause dermatitis. Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Sensitization**

No information available.

Germ Cell Mutagenicity

No information available.

Carcinogenicity

The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
KEROSENE 8008-20-6	A3	Group 3	-	-
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	A2	Group 1	-	X

2-BUTOXYETHANOL 111-76-2	A3	Group 3	-	-
-----------------------------	----	---------	---	---

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

The ingredients are not reproductive hazards.

Specific target organ systemic toxicity (single exposure)

May cause drowsiness or dizziness.

Specific target organ systemic toxicity (repeated exposure)

No information available.

Chronic toxicity

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. Prolonged skin contact may defat the skin and produce dermatitis. May cause adverse liver effects.

Target Organ Effects

Blood, Central nervous system, Eyes, Hematopoietic System, Kidney, Liver, Respiratory system, Skin.

Aspiration hazard

May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity

20.04411% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 5569 mg/kg

ATEmix (dermal) 2976 mg/kg

ATEmix (inhalation-dust/mist) 58.6 mg/l

ATEmix (inhalation-vapor) 17586 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PETROLEUM DISTILLATES 64742-47-8	-	45 mg/L LC50 Pimephales promelas 96h flow-through 2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static	-	-
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
2-BUTOXYETHANOL 111-76-2	-	1490 mg/L LC50 Lepomis macrochirus 96h static 2950 mg/L LC50 Lepomis macrochirus 96h	-	1000 mg/L EC50 Daphnia magna 48h

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	<=2.8
2-BUTOXYETHANOL 111-76-2	0.81

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D
or
LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PETROLEUM DISTILLATES	X	X	X	X	X	X	X	X
KEROSENE	X	X	X	X	X	X	X	X
NAPHTHENIC OIL, SEVERLY HYDROT	X	X	X	X	X	X	X	X
PROPANE/ISOBUTAN E/N-BUTANE	X	X	X	Not listed	X	X	X	X
2-BUTOXYETHANOL	X	X	X	X	X	X	X	X

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
2-BUTOXYETHANOL - 111-76-2	111-76-2	2.55882	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

No warning required.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KEROSENE 8008-20-6	X	X	X
2-BUTOXYETHANOL 111-76-2	X	X	X

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 2	Flammability 4	Physical Hazard 1	Personal protection B

Prepared By Regulatory Affairs
Issuing date 11-Jul-2014
Revision Date 11-Jul-2014
Revision Note
No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet